

SAFETY DATA SHEET

SECTION 1 - PRODUCT & COMPANY IDENTIFICATION

Product Name: S132 Product Code: S-132

Trade Name: HAPS Free Universal Primer Thinner

Adams Paint Mfg Company
1416 N University Ave
Lubbock, Tx 79415
Telephone Number: 806-763-2944
Web Site: adamspaintmfg.com

Emergency Contacts & Phone Numbers
Chemtrec: 800-424-9300
SDS Request Line: 806-763-2944

Product Use: See Product Data Sheet

Not recommended for: See Product Data Sheet

SECTION 2 - HAZARDS IDENTIFICATION

GHS Ratings:

Flammable liquid	2	Flash point < 23°C and initial boiling point > 35°C (95°F)
Skin corrosive	3	Reversible adverse effects in dermal tissue, Draize score: >= 1.5 < 2.3
Eye corrosive	2A	Eye irritant: Subcategory 2A, Reversible in 21 days
Mutagen	1B	Known to produce heritable mutations in human germ cells Subcategory 1B, Positive results: In vivo heritable germ cell tests in mammals, Human germ cell tests, In vivo somatic mutagenicity tests, combined with some evidence of germ cell mutagenicity
Carcinogen	1B	Presumed Human Carcinogen, Based on demonstrated animal carcinogenicity
Reproductive toxin	1B	Presumed, Based on experimental animals
Aspiration hazard	1	Aspiration Toxicity Category 1: Known (regarded)- human evidence - hydrocarbons with kinematic viscosity ? 20.5 mm ² /s at 40° C.

GHS Hazards

H225	Highly flammable liquid and vapour
H304	May be fatal if swallowed and enters airways
H316	Causes mild skin irritation
H319	Causes serious eye irritation
H340	May cause genetic defects
H350	May cause cancer
H360	May damage fertility or the unborn child

GHS Precautions

P201	Obtain special instructions before use
P202	Do not handle until all safety precautions have been read and understood
P210	Keep away from heat, sparks, open flames, hot surfaces and other ignition sources - No smoking
P233	Keep container tightly closed
P240	Ground and bond container and receiving equipment
P241	Use explosion-proof electrical, ventilating, lighting and equipment
P242	Use only non-sparking tools
P243	Take precautionary measures against static discharge
P264	Wash thoroughly after handling

P280	Wear protective gloves, protective clothing, eye protection and face protection
P281	Use personal protective equipment as required
P331	Do NOT induce vomiting
P301+P310	IF SWALLOWED: Immediately call a POISON CENTER or physician
P303+P361+P353	IF ON SKIN: Take off immediately all contaminated clothing. Rinse skin with water
P305+P351+P338	IF IN EYES: Rinse continuously with water for several minutes. Remove contact lenses if present and easy to do – continue rinsing
P308+P313	IF exposed or concerned: Get medical attention
P332+P313	If skin irritation occurs: Get medical attention
P337+P313	Get medical attention
P370+P378	In case of fire: Use dry chemical, foam, carbon dioxide or water fog for extinction
P405	Store locked up
P403+P235	Store in a well ventilated place. Keep cool
P501	Dispose of contents and container in accordance with local and national regulations

Signal Word: Danger



SECTION 3 - COMPOSITION INFORMATION ON INGREDIENTS

Chemical Name	CAS number	Weight Concentration %
Solvent naphtha, petroleum, light aliphatic	64742-89-8	50.00% - 60.00%
Solvent naphtha, petroleum, light aromatic	64742-95-6	10.00% - 20.00%
Acetone	67-64-1	10.00% - 20.00%
Isopropyl alcohol	67-63-0	10.00% - 20.00%
Benzene, 1,2,4-trimethyl-	95-63-6	5.00% - 10.00%
Cumene	98-82-8	0.10% - 1.00%
Ethylbenzene	100-41-4	0.10% - 1.00%

SECTION 4 - FIRST AID MEASURES

Inhalation: If inhaled, remove to fresh air. If not breathing, give artificial respiration or give oxygen by trained personnel. Seek immediate medical attention.

Eye Contact: Immediately flush eyes with plenty of water for 10 to 15 minutes. Get medical attention, if irritation or symptoms of overexposure persists.

Skin Contact: Immediately wash skin with soap and water. Get medical attention if irritation develops or persists.

Ingestion: If swallowed, DO NOT induce vomiting. Call physician or poison control center immediately. Never give anything by mouth to an unconscious person.

Other First Aid: Due to possible aspiration into lungs, DO NOT induce vomiting if ingested. Provide a glass of water to dilute the material in the stomach. If vomiting occurs naturally, have person lean forward to reduce risk of aspiration.

SECTION 5 - FIRE FIGHTING MEASURES

Flash Point: -20 C (-4 F)

LEL: 1.00

UEL: 13.00

Suitable Extinguishing Media: Use dry chemical, foam, carbon dioxide, or water fog to extinguish fire. Water may

not be effective to extinguish fire. Spattering of flammable liquid may result from spraying water.

Specific Hazards arising from the Chemical: Minimize breathing gases, vapors, fumes or decomposition products. at elevated temperatures, vapors can form an ignitable mixture with air. Vapors can flow along surfaces to distant ignition sources and flash back. Closed containers may explode when exposed to heat.

Protection of Firefighters: Water may be unsuitable as an extinguishing media, but helpful in keeping adjacent containers cool. If a leak or spill has ignited, use water spray to disperse the vapors and to protect the men attempting to stop leak.

Protective Equipment and Precautions for Firefighters: Wear self-contained breathing apparatus and full protective gear.

SECTION 6 - ACCIDENTAL RELEASE MEASURES

Personal Precautions: Use proper personal protective equipment as listed in Section 8.

Environmental Precautions: Avoid runoff into storm sewers, ditches and waterways.

Methods for Containment: Contain spilled liquid with sand or earth. DO NOT use combustible materials, such as sawdust.

Methods for Clean-up: Remove all sources of ignition. Provide ventilation. Absorb spill with inert material (dry sand or earth), collect spill with a non-sparking tool then place in a chemical waste container for disposal.

SECTION 7 - HANDLING AND STORAGE

Handling: Use with adequate ventilation. Avoid breathing vapor and contacts with eyes, skin and clothing. Material will accumulate static charges which may cause an electrical spark (ignition source), bond and ground containers when transferring material. Use spark-proof tools and explosion-proof equipment. Do not reuse containers without proper cleaning or reconditioning.

Hygiene Practices: Wash thoroughly after handling. Avoid contact with eyes and skin. Avoid inhaling vapor or mist.

Storage: Store in a cool dry, well ventilated area away from sources of heat, combustible materials and incompatible substances. Keep container tightly closed when not in use.

SECTION 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

Chemical Name / CAS No.	OSHA Exposure Limits	ACGIH Exposure Limits	Other Exposure Limits
Solvent naphtha, petroleum, light aliphatic 64742-89-8	Not Established	Not Established	Not Established
Solvent naphtha, petroleum, light aromatic 64742-95-6	Not Established	Not Established	Not Established
Acetone 67-64-1	1000 ppm TWA; 2400 mg/m3 TWA	750 ppm STEL 500 ppm TWA	NIOSH: 250 ppm TWA; 590 mg/m3 TWA
Isopropyl alcohol 67-63-0	400 ppm TWA; 980 mg/m3 TWA	400 ppm STEL 200 ppm TWA	NIOSH: 400 ppm TWA; 980 mg/m3 TWA 500 ppm STEL; 1225 mg/m3 STEL
Benzene, 1,2,4-trimethyl- 95-63-6	Not Established	Not Established	NIOSH: 25 ppm TWA; 125 mg/m3 TWA
Cumene 98-82-8	50 ppm TWA; 245 mg/m3 TWA	50 ppm TWA	NIOSH: 50 ppm TWA; 245 mg/m3 TWA
Ethylbenzene 100-41-4	100 ppm TWA; 435 mg/m3 TWA	20 ppm TWA	NIOSH: 100 ppm TWA; 435 mg/m3 TWA 125 ppm STEL; 545 mg/m3 STEL

Engineering Controls: Use appropriate engineering control such as process enclosures, local exhaust ventilation or

other engineering controls to control airborne levels below recommended exposure limits. Good general ventilation should be sufficient to control airborne levels. Where such systems are not effective, wear suitable personal protective equipment, which performs satisfactorily and meets OSHA or other recognized standards. Consult with local procedures for selection, training, inspection and maintenance of the personal protective equipment.

Eye / Face Protection: Wear protective glasses or splash goggles as described by 29 CFR 1910.133, OSHA eye and face protection regulations.

Skin Protection: Chemical-resistant gloves and chemical goggles, face-shield and synthetic apron or coveralls should be used to prevent contact with eye, skin or clothing.

Respiratory Protection: A NIOSH-approved air-purifying respirator with an organic vapor cartridge or canister may be permissible under certain circumstances where airborne concentrations are expected to exceed exposure limits. Protection provided by air-purifying respirators is limited. Use a positive-pressure, air-supplied respirator if there is any potential for uncontrolled release, exposure levels are not known or any other circumstances where air-purifying respirators may not provide adequate protection.

General Hygiene Considerations: Avoid breathing vapor or mist. Avoid contact with eyes and skin. Wash thoroughly after handling and before eating or drinking.

SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

<p>Appearance: Liquid</p> <p>Vapor Pressure: 22.0 mmHg</p> <p>Vapor Density: Heavier than air</p> <p>Lbs / Gallon: 6.50</p> <p>Freezing point: No Data</p> <p>Boiling range: 56°C</p> <p>Evaporation rate: Slower than Ether</p> <p>Explosive Limits: 1% - 13%</p> <p>Autoignition temperature: 280°C</p> <p>Viscosity: No Data</p>	<p>Odor: Aromatic, sweet</p> <p>Odor threshold: No Data</p> <p>pH: No Data</p> <p>Melting point: No Data</p> <p>Solubility: Moderate</p> <p>Flash point: -4 F, -20 C</p> <p>Flammability: Flammable Liquid Class IB</p> <p>Partition coefficient (n-octanol/water): No Data</p> <p>Decomposition temperature: No Data</p> <p>VOC g/l: 776.919</p>
-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------	-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

SECTION 10 - STABILITY AND REACTIVITY

Chemical Stability: Stable

Conditions to Avoid: Heat, flames, sparks and other ignition sources.

Incompatible Materials: Avoid contact with strong oxidizing agents.

Hazardous Decomposition Products: Incomplete combustion may produce carbon monoxide and other toxic gases.

Hazardous Polymerization: Will not occur.

SECTION 11 - TOXICOLOGICAL INFORMATION

Mixture Toxicity

Dermal Toxicity LD50: 4,629mg/kg

Inhalation Toxicity LC50: 134mg/L

Component Toxicity

64742-89-8 Solvent naphtha, petroleum, light aliphatic

Oral LD50: 5,000 mg/kg (Mouse) Dermal LD50: 3,000 mg/kg (Rabbit)

67-63-0 Isopropyl alcohol

Oral LD50: 1,870 mg/kg (Rat) Dermal LD50: 4,059 mg/kg (Rabbit)

100-41-4 Ethylbenzene

Oral LD50: 3,500 mg/kg (Rat) Inhalation LC50: 17 mg/L (Rat)

Miscellaneous Toxicological Information:

Notice: Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal.

<u>CAS Number</u>	<u>Description</u>	<u>% Weight</u>	<u>Carcinogen Rating</u>
64742-95-6	Solvent naphtha, petroleum, light aromatic	10 to 20%	Solvent naphtha, petroleum, light aromatic: EU REACH: Present (P)
100-41-4	Ethylbenzene	.1 to 1.0%	Ethylbenzene: IARC: Possible human carcinogen OSHA: listed
98-82-8	Cumene	.1 to 1.0%	Cumene: IARC: Possible human carcinogen OSHA: listed
64742-89-8	Solvent naphtha, petroleum, light aliphatic	50 to 60%	Solvent naphtha, petroleum, light aliphatic: EU REACH: Present (P)

SECTION 12 - ECOLOGICAL INFORMATION

No additional information provided for this product. See Section 3 for chemical specific data.

Component Ecotoxicity

Solvent naphtha, petroleum, light aliphatic	72 Hr EC50 Pseudokirchneriella subcapitata: 4700 mg/L
Solvent naphtha, petroleum, light aromatic	96 Hr LC50 Oncorhynchus mykiss: 9.22 mg/L 48 Hr EC50 Daphnia magna: 6.14 mg/L
Acetone	96 Hr LC50 Oncorhynchus mykiss: 4.74 - 6.33 mL/L; 96 Hr LC50 Pimephales promelas: 6210 - 8120 mg/L [static]; 96 Hr LC50 Lepomis macrochirus: 8300 mg/L 48 Hr EC50 Daphnia magna: 10294 - 17704 mg/L [Static]; 48 Hr EC50 Daphnia magna: 12600 - 12700 mg/L
Isopropyl alcohol	96 Hr LC50 Pimephales promelas: 9640 mg/L [flow-through]; 96 Hr LC50 Pimephales promelas: 11130 mg/L [static]; 96 Hr LC50 Lepomis macrochirus: >1400000 µg/L 48 Hr EC50 Daphnia magna: 13299 mg/L 96 Hr EC50 Desmodemus subspicatus: >1000 mg/L; 72 Hr EC50 Desmodemus subspicatus: >1000 mg/L
Benzene, 1,2,4-trimethyl-	96 Hr LC50 Pimephales promelas: 7.19 - 8.28 mg/L [flow-through] 48 Hr EC50 Daphnia magna: 6.14 mg/L
Cumene	96 Hr LC50 Pimephales promelas: 6.04 - 6.61 mg/L [flow-through]; 96 Hr LC50 Oncorhynchus mykiss: 4.8 mg/L [flow-through]; 96 Hr LC50 Oncorhynchus mykiss: 2.7 mg/L [semi-static]; 96 Hr LC50 Poecilia reticulata: 5.1 mg/L [semi-static] 48 Hr EC50 Daphnia magna: 0.6 mg/L; 48 Hr EC50 Daphnia magna: 7.9 - 14.1 mg/L [Static] 72 Hr EC50 Pseudokirchneriella subcapitata: 2.6 mg/L

Ethylbenzene

96 Hr LC50 Oncorhynchus mykiss: 11.0 - 18.0 mg/L [static]; 96 Hr LC50 Oncorhynchus mykiss: 4.2 mg/L [semi-static]; 96 Hr LC50 Pimephales promelas: 7.55 - 11 mg/L [flow-through]; 96 Hr LC50 Lepomis macrochirus: 32 mg/L [static]; 96 Hr LC50 Pimephales promelas: 9.1 - 15.6 mg/L [static]; 96 Hr LC50 Poecilia reticulata: 9.6 mg/L [static]
48 Hr EC50 Daphnia magna: 1.8 - 2.4 mg/L
72 Hr EC50 Pseudokirchneriella subcapitata: 4.6 mg/L; 96 Hr EC50 Pseudokirchneriella subcapitata: >438 mg/L; 72 Hr EC50 Pseudokirchneriella subcapitata: 2.6 - 11.3 mg/L [static]; 96 Hr EC50 Pseudokirchneriella subcapitata: 1.7 - 7.6 mg/L [static]

SECTION 13 - DISPOSAL CONSIDERATIONS

Waste Disposal: Consult with the US EPA Guidelines listed in 40 CFR Part 261.3 for the classification of hazardous waste prior to disposal. Furthermore, consult with your state and local waste requirements or guidelines, if applicable, to ensure compliance. Arrange disposal in accordance to the EPA and / or state and local guidelines .

SECTION 14 - TRANSPORT INFORMATION

<u>Agency</u>	<u>Proper Shipping Name</u>	<u>UN Number</u>	<u>Packing Group</u>	<u>Hazard Class</u>
DOT	Paint Related Material	1263	II	3

SECTION 15 - REGULATORY INFORMATION

Additional regulatory listings, where applicable.

CERCLA RQ:

<u>Component</u>	<u>RQ (lbs)</u>
Acetone	5000
Cumene	5000
Ethylbenzene	1000

SARA 311/312 Hazard Classes: Acute, Fire

State of California Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65): WARNING!

This product contains the following chemicals which are listed by the State of California as carcinogenic or a reproductive toxin:

100-41-4 Ethylbenzene 0.1 to 1.0 % Carcinogen
98-82-8 Cumene 0.1 to 1.0 % Carcinogen

SARA 302 Components:

- None

SARA 313 TOXIC CHEMICALS:

100-41-4 Ethylbenzene 0.1 to 1.0 %
98-82-8 Cumene 0.1 to 1.0 %
95-63-6 Benzene, 1,2,4-trimethyl- 5 to 10 %
67-63-0 Isopropyl alcohol 10 to 20 %

Toxic Substances Control Act (TSCA): All chemicals except those listed below appear in the Toxic Substances Control Act Chemical Substance Inventory.

- None

SECTION 16 - OTHER INFORMATION

The information and recommendations contained herein are based upon data believed to be correct. However, no guarantee or warranty of any kind, expressed or implied, is made with respect to the information contained herein. We accept no responsibility and disclaim all liability for any harmful effects which may be caused by exposure to our products. Customers/users of this product must comply with all applicable health and safety laws, regulations and orders.

Reviewer Revision

Date Prepared: 6/17/2015