

SAFETY DATA SHEET

SECTION 1 - PRODUCT & COMPANY IDENTIFICATION

Product Name: 399 Phenolic Epoxy Tank Lining Product Code: 399-Activator Black

Trade Name: 399-Activator Black

Adams Paint Mfg Company
1416 N University Ave
Lubbock, Tx 79415
Telephone Number: 806-763-2944
Web Site: adamspaintmfg.com

Emergency Contacts & Phone Numbers
Chemtrec: 800-424-9300
SDS Request Line: 806-763-2944

Product Use: See Product Data Sheet

Not recommended for: See Product Data Sheet

SECTION 2 - HAZARDS IDENTIFICATION

GHS Ratings:

Skin corrosive	1A	Destruction of dermal tissue: Exposure < 3 min. Observation < 1 hour, visible necrosis in at least one animal
Eye corrosive	1	Serious eye damage: Irreversible damage 21 days after exposure, Draize score: Corneal opacity ≥ 3 , Iritis > 1.5
Respiratory sensitizer	1	Respiratory sensitizer
Skin sensitizer	1	Skin sensitizer
Carcinogen	2	Limited evidence of human or animal carcinogenicity
Reproductive toxin	1B	Presumed, Based on experimental animals

GHS Hazards

H314	Causes severe skin burns and eye damage
H317	May cause an allergic skin reaction
H318	Causes serious eye damage
H334	May cause allergy or asthma symptoms or breathing difficulties if inhaled
H351	Suspected of causing cancer
H360	May damage fertility or the unborn child

GHS Precautions

P201	Obtain special instructions before use
P202	Do not handle until all safety precautions have been read and understood
P260	Do not breathe dust, fumes, gas, mist, vapors or spray
P261	Avoid breathing dust, fumes, gas, mist, vapors or spray
P264	Wash thoroughly after handling
P272	Contaminated work clothing should not be allowed out of the workplace
P280	Wear protective gloves, protective clothing, eye protection and face protection
P281	Use personal protective equipment as required
P285	In case of inadequate ventilation wear respiratory protection
P310	Immediately call a POISON CENTER or physician
P321	Specific treatment (see Section 4 of SDS on this label)
P363	Wash contaminated clothing before reuse
P301+P330+P331	IF SWALLOWED: Rinse mouth. Do NOT induce vomiting
P302+P352	IF ON SKIN: Wash with soap and water
P303+P361+P353	IF ON SKIN: Take off immediately all contaminated clothing. Rinse skin with water
P304+P340	IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing

P304+P341	IF INHALED: If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing
P305+P351+P338	IF IN EYES: Rinse continuously with water for several minutes. Remove contact lenses if present and easy to do – continue rinsing
P308+P313	IF exposed or concerned: Get medical attention
P333+P313	If skin irritation or a rash occurs: Get medical attention
P342+P311	Call a POISON CENTER or physician
P405	Store locked up
P501	Dispose of contents and container in accordance with local and national regulations

Signal Word: Danger



SECTION 3 - COMPOSITION INFORMATION ON INGREDIENTS

Chemical Name	CAS number	Weight Concentration %
Formaldehyde, polymer with benzenamine, hydrogenated	135108-88-2	30.00% - 40.00%
Benzyl alcohol	100-51-6	30.00% - 40.00%
Diethylenetriamine	111-40-0	10.00% - 20.00%
1,3-Benzenedimethanamine	1477-55-0	5.00% - 10.00%
Bisphenol A	80-05-7	5.00% - 10.00%
Carbon black	1333-86-4	0.10% - 1.00%

SECTION 4 - FIRST AID MEASURES

Inhalation: Move exposed person to fresh air. Keep person warm and at rest. If not breathing, give artificial respiration or give oxygen by trained personnel. Seek immediate medical attention.

Eye Contact: Immediately flush eyes with plenty of water for at least 15 minutes, occasionally lifting upper and lower eyelids. Check for and remove any contact lenses. Get medical attention.

Skin Contact: Flush contaminated skin with plenty of water. Remove contaminated clothing and shoes. Wash contaminated clothing thoroughly with water before removing or wear gloves. Continue to rinse for at least 10 minutes. In the event of any complaints or symptoms, avoid further exposure. Get medical attention.

Ingestion: Wash out mouth with water. Move exposed person to fresh air. Keep person warm and at rest. DO NOT induce vomiting unless directed to do so by medical personnel. If vomiting occurs, the head should be kept low so that vomit does not enter the lungs. Get medical attention. Never give anything by mouth to an unconscious person.

Overexposure Effects: Corrosive - Causes skin and eye burns. May cause allergic skin and respiratory reactions. Harmful if absorbed through skin. May be harmful if swallowed.

Notes to Physician: No specific treatment. Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.

SECTION 5 - FIRE FIGHTING MEASURES

Flash Point: 103 C (217 F)

LEL:

UEL:

Suitable Extinguishing Media: Use carbon dioxide, foam, dry chemical or water spray to extinguishing fire. Do not use water jet.

Specific Hazards arising from the Chemical: Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken involving any personal risk or without suitable training.

Hazardous Combustion Products: Decomposition products may be toxic.

Protection of Firefighters: Water may be unsuitable as an extinguishing media, but helpful in keeping adjacent containers cool. If a leak or spill has ignited, use water spray to disperse the vapors and to protect the men attempting to stop leak.

Protective Equipment and Precautions for Firefighters: Wear self-contained breathing apparatus and full protective gear.

SECTION 6 - ACCIDENTAL RELEASE MEASURES

Personal Precautions: No action shall be taken involving personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Avoid breathing vapor or mist. Provide adequate ventilation. Use proper personal protective equipment as listed in Section 8.

Environmental Precautions: Avoid runoff into storm sewers, ditches and waterways. Inform the relevant authorities if the product has caused environmental pollution.

Methods and Material for Containment and Clean Up: Stop leak if without risk. Move containers from spill area. Absorb with liquid-binding material (sand, diatomite, acid binders or other an inert material) and place in an appropriate waste disposal container. Dispose of via a licensed waste disposal contractor.

SECTION 7 - HANDLING AND STORAGE

Handling: Put on appropriate personal protective equipment (see section 8). Workers should wash hands and face before eating, drinking and smoking. Do not get in eyes or on skin or clothing. Do not breath vapor or mist. Do not ingest. Use only with adequate ventilation. Keep container closed when not in use. Do not reuse container.

Storage: Store in original container in a well ventilated area away from incompatible materials. Keep container tightly closed when not in use to prevent moisture absorption and contamination. Use appropriate containment to avoid environmental contamination.

SECTION 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

Chemical Name / CAS No.	OSHA Exposure Limits	ACGIH Exposure Limits	Other Exposure Limits
Formaldehyde, polymer with benzenamine, hydrogenated 135108-88-2	Not Established	Not Established	Not Established
Benzyl alcohol 100-51-6	Not Established	Not Established	Not Established
Diethylenetriamine 111-40-0	Not Established	1 ppm TWA	NIOSH: 1 ppm TWA; 4 mg/m3 TWA
1,3-Benzenedimethanamine 1477-55-0	Not Established	0.1 mg/m3 Ceiling	NIOSH: 0.1 mg/m3 Ceiling
Bisphenol A 80-05-7	Not Established	Not Established	Not Established
Carbon black 1333-86-4	3.5 mg/m3 TWA	3 mg/m3 TWA (inhalable fraction)	NIOSH: 3.5 mg/m3 TWA; 0.1 mg/m3 TWA (Carbon black in presence of Polycyclic aromatic hydrocarbons, as PAH)

Engineering Controls: Use appropriate engineering control such as process enclosures, local exhaust ventilation or other engineering controls to control airborne levels below recommended exposure limits. Good general ventilation should be sufficient to control airborne levels. Where such systems are not effective, wear suitable personal protective equipment, which performs satisfactorily and meets OSHA or other recognized standards. Consult with local procedures for selection, training, inspection and maintenance of the personal protective equipment.

Eye / Face Protection: Wear protective glasses or splash goggles as described by 29 CFR 1910.133, OSHA eye and face protection regulations.

Skin Protection: Chemical-resistant gloves and chemical goggles, face-shield and synthetic apron or coveralls should be used to prevent contact with eye, skin or clothing.

Respiratory Protection: A NIOSH-approved air-purifying respirator with an organic vapor cartridge or canister may be permissible under certain circumstances where airborne concentrations are expected to exceed exposure limits. Protection provided by air-purifying respirators is limited. Use a positive-pressure, air-supplied respirator if there is any potential for uncontrolled release, exposure levels are not known or any other circumstances where air-purifying respirators may not provide adequate protection.

General Hygiene Considerations: Avoid breathing vapor or mist. Avoid contact with eyes and skin. Wash thoroughly after handling and before eating or drinking. Appropriate techniques should be used to remove potentially contaminated clothing. Wash contaminated clothing before reusing.

SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Appearance: Liquid	Odor: Amine
Vapor Pressure: 0.20 mmHg	Odor threshold: No Data
Vapor Density: Heavier than air	pH: No Data
Lbs / Gallon: 8.81	Melting point: No Data
Freezing point: No Data	Solubility: Miscible
Boiling range: 205°C	Flash point: 217 F, 103 C
Evaporation rate: Slower than Ether	Flammability: No Data
Explosive Limits: 0%	Partition coefficient (n-octanol/water): No Data
Autoignition temperature: 399°C	Decomposition temperature: No Data
Viscosity: No Data	VOC g/l: 6.346

SECTION 10 - STABILITY AND REACTIVITY

Chemical Stability: Stable under normal temperatures and pressures.

Conditions to Avoid: No further relevant information available.

Incompatible Materials: Avoid contact with peroxides, oxidizing agents, acids, alkalis, copper and its alloys.

Hazardous Decomposition Products: Decomposition products may include carbon oxides, nitrogen oxides, ammonia, aldehydes.

Hazardous Polymerization: No further relevant information available.

SECTION 11 - TOXICOLOGICAL INFORMATION

Mixture Toxicity

Oral Toxicity LD50: 2,043mg/kg

Dermal Toxicity LD50: 2,485mg/kg

Inhalation Toxicity LC50: 27mg/L

Component Toxicity

100-51-6

Benzyl alcohol

Oral LD50: 1,230 mg/kg (Rat) Dermal LD50: 2 g/kg (Rabbit) Inhalation LC50: 9 mg/L (Rat)

111-40-0

Diethylenetriamine

Oral LD50: 1,080 mg/kg (Rat) Dermal LD50: 672 mg/kg (Rabbit) Inhalation LC50: 70 mg/L (Rat)

1477-55-0

1,3-Benzenedimethanamine

Oral LD50: 660 mg/kg (Rat) Dermal LD50: 2 g/kg (Rabbit) Inhalation LC50: 700 ppm (Rat)

80-05-7

Bisphenol A

Oral LD50: 3,300 mg/kg (Rat) Dermal LD50: 3,000 mg/kg (Rabbit)

<u>CAS Number</u>	<u>Description</u>	<u>% Weight</u>	<u>Carcinogen Rating</u>
1333-86-4	Carbon black	.1 to 1.0%	Carbon black: NIOSH: potential occupational carcinogen IARC: Possible human carcinogen OSHA: listed

SECTION 12 - ECOLOGICAL INFORMATION

No additional information provided for this product. See Section 3 for chemical specific data.

Component Ecotoxicity

Benzyl alcohol	96 Hr LC50 Pimephales promelas: 460 mg/L [static]; 96 Hr LC50 Lepomis macrochirus: 10 mg/L [static] 48 Hr EC50 water flea: 23 mg/L
Diethylenetriamine	96 Hr LC50 Poecilia reticulata: 248 mg/L [static]; 96 Hr LC50 Poecilia reticulata: 1014 mg/L [semi-static] 48 Hr EC50 Daphnia magna: 16 mg/L 72 Hr EC50 Pseudokirchneriella subcapitata: 1164 mg/L; 96 Hr EC50 Pseudokirchneriella subcapitata: 345.6 mg/L; 96 Hr EC50 Desmodemus subspicatus: 592 mg/L
Bisphenol A	96 Hr LC50 Pimephales promelas: 3.6 - 5.4 mg/L [flow-through]; 96 Hr LC50 Pimephales promelas: 4.0 - 5.5 mg/L [static]; 96 Hr LC50 Oncorhynchus mykiss: 4 mg/L; 96 Hr LC50 Brachydanio rerio: 9.9 mg/L [static] 48 Hr EC50 Daphnia magna: 10.2 mg/L; 48 Hr EC50 Daphnia magna: 3.9 mg/L; 48 Hr EC50 Daphnia magna: 9.2 - 11.4 mg/L [Static] 96 Hr EC50 Pseudokirchneriella subcapitata: 2.5 mg/L

SECTION 13 - DISPOSAL CONSIDERATIONS

Waste Disposal: Consult with the US EPA Guidelines listed in 40 CFR Part 261.3 for the classification of hazardous waste prior to disposal. Furthermore, consult with your state and local waste requirements or guidelines, if applicable, to ensure compliance. Arrange disposal in accordance to the EPA and / or state and local guidelines.

SECTION 14 - TRANSPORT INFORMATION

<u>Agency</u>	<u>Proper Shipping Name</u>	<u>UN Number</u>	<u>Packing Group</u>	<u>Hazard Class</u>
DOT	Paint	3066	II	8

SECTION 15 - REGULATORY INFORMATION

Additional regulatory listings, where applicable.

CERCLA RQ:

<u>Component</u>	<u>RQ (lbs)</u>
None	

SARA 311/312 Hazard Classes: Acute, Chronic, Fire

State of California Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65): WARNING!

This product contains the following chemicals which are listed by the State of California as carcinogenic or a reproductive toxin:

1333-86-4 Carbon black 0.1 to 1.0 % Carcinogen

SARA 302 Components:

- None

SARA 313 TOXIC CHEMICALS:

80-05-7 Bisphenol A 5 to 10 %

Toxic Substances Control Act (TSCA): All chemicals except those listed below appear in the Toxic Substances Control Act Chemical Substance Inventory.

- None

SECTION 16 - OTHER INFORMATION

The information and recommendations contained herein are based upon data believed to be correct. However, no guarantee or warranty of any kind, expressed or implied, is made with respect to the information contained herein. We accept no responsibility and disclaim all liability for any harmful effects which may be caused by exposure to our products. Customers/users of this product must comply with all applicable health and safety laws, regulations and orders.

Reviewer Revision

Date Prepared: 6/17/2015